

SERVO 2W GEAR OIL

GRADES AVAILABLE - SERVO 2W GEAR OIL

DESCRIPTION

Servo 2W Gear Oil oils are used as gear lubricants. These oils are blended from selected base stocks and contain specific additive package to provide anti-wear, anti-rust and anti-corrosion characteristics.

APPLICATION

Servo 2W Gear oils are recommended for Gear Lubrication of 2 wheelers.

PERFORMANCE BENEFITS

- Satisfy the lubrication requirements of gears in 2 stroke 2 wheelers
- Provide protection against wear.
- Give long service life even under high temperature operation since it has excellent oxidation stability.
- Provide good protection against corrosion.

APPROVAL

Approved for the following Moped Gear Boxes by M/s. TVS Motor Company Ltd.

- TVS XL Super
- TVS XL Super (Heavy Duty)

CHARACTERISTICS

SAE GRADE	40
Kinematic Viscosity cSt @ 100°C	13 –15
Viscosity Index, Min.	90
Flash point (COC), °C Min.	226
Pour Point, °C Max.	(-) 6

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tsservices@indianoil.co.in OR tech_services@indianoil.co.in

