

SERVO GREASE ALT

GRADES AVAILABLE – SERVOGREASE ALT

DESCRIPTION

Servo Grease ALT is a premium quality lithium soap, multi-purpose automotive grease, with high drop point, good thermal and structural stability and also having resistance against water wash out. With its smooth structure and high degree of resistance against oxidation and rusting/corrosion it is an ideal product for all grease lubricated parts of automotive equipment. This grease is specially developed for general chassis lubrication and water pump lubrication of Ashok Leyland vehicles.

APPLICATION

Servo Grease ALT is recommended for water pump, chassis fittings, slack adjuster, shackle pins, pedal shafts of Ashok Leyland vehicles.

PERFORMANCE BENEFITS

- Provides excellent resistance to structural and consistency changes, over wide range of temperatures but remains in place despite severe working or sustained shock impact
- Has excellent low and high temperature properties. It can be dispensed at low temperatures and will maintain adequate stay-put property at the higher temperatures encountered in service
- Resists effectively, water wash out in use, assuring adequate lubrication over extended service periods
- Provides resistance to oxidation, rust and corrosion.

PERFORMANCE STANDARDS

Servo Grease ALT meets IS:12203:1987 (Reaffirmed 1993)

MANUFACTURER'S APPROVAL

- Ashok Leyland Ltd., Chennai – Greasing frequency every 8000 KMs.

CHARACTERISTICS

GRADE	Grease ALT
Colour	Brown
Structure	Smooth
Soap Type	Lithium
Worked Penetration, @25°C, (60 Strokes)	270-310
Drop Point, °C Min.	180

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

