

Product Data Sheet

Servo Raftaar 15W-40

Premium BS VI Diesel Engine Oil



Description

Servo Raftaar 15W-40 is Eco-friendly premium diesel engine oil for all types of diesel vehicles. The oil is having optimized performance package to give excellent thermo oxidative resistance & soot dispersance. It meets API CK-4 requirements and is recommended for all diesel vehicles having sophisticated after-treatment devices like SCR & DPF.

Performance, Features and Benefits

- Provides maximum protection from wear and deposits & high engine cleanliness.
- Superior anti oxidation properties and control on oil consumption
- Excellent all weather performance due to improved cold weather properties.
- Has the potential of drain interval up to 60000 km in heavy duty engines
- Facilitates reduction of Carbon dioxide by 10% in ecosystem leading to reduction in carbon footprints
- Compatible with after treatment devices like SCR & DPF

Application

Servo Raftaar 15W-40 is BS VI compliant oil recommended for passenger diesel cars & SUVs as well as commercial diesel vehicles operating on on-highway and off-highway equipment. These oils are also suitable for vehicles running with bio-diesel (up to 10%).

Approvals / Performance Standards / Recommendations

Servo Raftaar 15W-40 meets the requirements of API CK-4 performance level

Typical Physical Characteristics

Servo Raftaar	Method	15W-40
Appearance	Visual	Clear & Bright
Colour	ASTM D-1500	5.0
Flash point COC , deg °C	ASTM D-92	229
Pour Point, deg °C	ASTM D-97	(-) 36
Kinematic viscosity at 100°C, cST	ASTM D-445	14.24
Viscosity Index	ASTM D-2270	139
HTHS @ 150 °C , mPas	ASTM D-4863	4.02
Total base number, mg KOH/g	ASTM D-2896	9.4
Foam test; Tend/Stab, ml		
Seq. I		10/0
Seq. II	ASTM D-892	20/0
Seq. III		10/0
Sulfated ash , % wt	ASTM D-874	0.96

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

11 AUG 2021

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051

E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | <https://cx.indianoil.in/>