

SERVO[®] PRODUCT DATA SHEET

SERVO GEAR AXLE 85W-140



GRADES AVAILABLE - SERVO GEAR AXLE 85W-140

DESCRIPTION

Servo Gear Axle 85W-140 oil is a heavy duty multigraded special purpose gear lubricant. This oil is blended from selected base stocks and contain specific additive package to provide extreme pressure, anti-rust-corrosion characteristics.

APPLICATION

Servo Gear Axle 85W-140 oil is recommended differentials / axles of heavy commercial vehicles.

PERFORMANCE BENEFITS

- Satisfy the lubrication requirements of different axles.
- Provide protection against wear, due to good EP characteristics
- Give long service life even under high temperature operation since it has excellent oxidation stability.
- Provide good protection against corrosion.
- Has potential for extended drain period compared to conventional API GL 5 oils.

PERFORMANCE STANDARDS

Servo Gear Axle 85W-140 meets

- API Service GL 5
- API MT 1
- MIL- PRF – 2105E

CHARACTERISTICS

SAE GRADE	85W-140
Kinematic Viscosity cSt @ 100°C	25 – 27
Viscosity Index, Min.	90
Flash point (COC), °C Min.	180
Pour Point, °C Max.	(-) 18

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

