



SERVOGEM ALT

GRADES AVAILABLE – SERVOGEM ALT

DESCRIPTION

Servogem ALT is a premium quality, lithium soap, automotive Wheel Bearing grease. The grease is manufactured from high viscosity index base oils and select additives with superior performance benefits.

APPLICATION

This grease is specially developed for the lubrication of Wheel Bearings of Ashok Leyland commercial vehicles to give longer service life.

PERFORMANCE BENEFITS

- Excellent resistance to water washout
- Superior oxidation and structural stability
- High degree of antirust and anticorrosion properties.
- Give outstanding performance under varying operating conditions.
- Suitable for lubrication under sub-zero (-25°C) to reasonably high (140°C) temperature conditions.
- **Gives longer service life compares to conventional wheel bearing greases**

PERFORMANCE STANDARDS

Meets specification of Association of American Railroads (AAR-M-942-81) with deviation in consistency and passes SKF Emscor corrosion test and WD-17-MISE-92 specifications.

APPROVAL:

Servogem ALT is approved by

- Ashok Leyland Ltd, Chennai-Grease change every 48000 Kms.

NLGI GRADE	Servogem ALT
Colour	Brown
Structure	Smooth
Soap Type	Lithium
Worked Penetration @ 25°C, (60 Strokes)	220-250
Drop Point, °C, Min.	180

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tsservices@indianoil.co.in OR tech_services@indianoil.co.in

