



## **GRADES AVAILABLE - LANCER COOLANT**

| <b>DESCRIPTION</b><br>Lancer Coolant is a triple action long life<br>radiator coolant prepared from selected<br>ingredients to meet the requirement of<br>Lancer cars.   | <b>APPLICATION</b><br>Lancer Coolant is recommended for Lancer cars for desired performance 30 parts of fluid to be diluted with 70 parts of distilled water.   |
|--|---|
| <ul> <li><b>PERFORMANCE BENEFITS</b></li> <li>Does not boil and vaporise in the hottest summer or freeze in swear winter.</li> <li>Prevents corrosion of radiator coolant and other parts.</li> <li>Increases cooling efficiency.</li> <li>Reduces maintenance costs and increases radiator life.</li> </ul> | <ul> <li>PERFORMANCE STANDARDS</li> <li>Meets specification EX-64113-BF 4 of M/s.<br/>Hindustan Motors Lancer.</li> <li>APPROVAL</li> <li>As Genuine Coolant by Hindustan<br/>Motors for Lancer vehicles</li> </ul> |

## CHARACTERISTICS

| Appearance                            | Green with yellow fluorescence |
|---------------------------------------|--------------------------------|
| Boiling Point, °C, Min                | 155                            |
| Freezing Point                        |                                |
| 30% Volume Solution, °C               | (-) 14                         |
| 50% Volume Solution, °C               | (-) 34                         |
| PH of 30% v/v Soln in Distilled water | 7.5 - 8.5                      |

## **HEALTH & SAFETY**

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest Office OR: Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051 E-Mail – tservices@indianoil.co.in OR tech\_services@indianoil.co.in