SERVO[®] product data sheet MARUTI GENUINE OIL



GRADES AVAILABLE – MARUTI GENUINE OIL

DESCRIPTION	APPLICATION
Maruti Genuine Oil is high performance engine oil for new generation petrol vehicles. These oils are blended from high viscosity index base stocks and contain additives to meet the stated performance standards. This oil has been extensively evaluated under tough field driving condition.	Maruti Genuine Oil is recommended for entire Maruti range of petrol vehicles. It is also suitable for other Indian cars.
PERFORMANCE BENEFITS	PERFORMANCE STANDARDS
 Superior performance in terms of oxidation stability, dispersancy characteristics and energy efficiency. Excellent sludge control and extra wear protection at high temperatures and severe operating conditions. Outstanding overall engine cleanliness and also provide long engine life. Fuel savings and low oil top up. Catalytic Convertor Compatible. 	 API SF in gasoline and CD in diesel service. US Military MIL-L-46152 B E-PL 2 / E-DL 2 of IS: 13656- 2002. APPROVAL Maruti Udyog Ltd for all petrol vehicles i.e. Maruti 800/ Van / Gypsy/ Esteem/ Wagon R / Zen / Alto / Swift, etc.

CHARACTERISTICS

SAE GRADE	20W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.5
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 21
TBN, mg KOH/gm	5 - 7

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR :

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051 E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in