SERVO[®] product data sheet SERVO SUPERIOR XEE



GRADES AVAILABLE - -SERVO SUPERIOR XEE 10W-30, 10W-40, 15W-40, 20W-50

DESCRIPTION	APPLICATION		
Servo Superior XEE oils are high performance engine oil for new generation petrol and diesel vehicles. These oils are blended from high viscosity index base stocks and contain additives to meet the stated performance standards.	Servo Superior XEE oils are recommended for new generation passenger cars using petro and diesel.		
PERFORMANCE BENEFITS	PERFORMANCE STANDARDS		
 Superior performance in terms of oxidation stability, dispersancy characteristics and energy efficiency. Excellent sludge control and extra wear protection at high temperatures and severe operating conditions. Outstanding overall engine cleanliness and also provide long engine life. Fuel savings and low oil top up. Catalytic Converter Compatible. 	☞ API SG		

CHARACTERISTICS

SAE GRADE	10W-30	10W-40	15W-40	20W-50
Kin. Viscosity @ 100°C, cSt	9.5 – 11.5	13.5 – 15.5	13.5 – 15.5	17.5 – 19.5
Viscosity Index, Min.	135	140	135	115
Flash Point, COC, °C, Min	200	190	200	200
Pour Point, °C, Max	(-) 27	(-) 27	(-) 24	(-) 21
TBN, mg KOH/gm	6.0 - 8.0	8 – 10.5	10.2 – 12.0	7.0 – 8.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd.,G-9,Ali Yavar Jung Marg, Bandra (E), Mumbai–400 051 E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in