

SERVO XEE SL

GRADES AVAILABLE - -SERVO XEE SL 5W-20, 10W-40

DESCRIPTION

Servo XEE SL oils are premium long life, high performance fuel economy engine oil for new generation petrol vehicles. These oils are blended from high viscosity index base stocks and contain additives to meet the highest quality performance standard.

APPLICATION

Servo XEE SL oils are recommended for new generation imported and Indian passenger cars using petrol.

PERFORMANCE BENEFITS

- ☞ Superior wear protection.
- ☞ Superior deposit control.
- ☞ Extended component life.
- ☞ Excellent engine cleanliness.
- ☞ Lower oil consumption
- ☞ Better Fuel Economy
- ☞ Catalytic Convertor Compatible.

PERFORMANCE STANDARDS

- ☞ API SL in gasoline service.
- ☞ Comply with ILSAC GF-3 Performance.

CHARACTERISTICS

SAE GRADE	5W-20	10W-40
Kin. Viscosity @ 100°C, cSt	8.0 – 9.3	13.5 – 15.5
Viscosity Index, Min	145	135
Flash Point, COC, °C, Min	190	200
TBN, mg KOH/gm	7.0	7.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

