SERVO [®] product data sheet

GRADES AVAILABLE - SERVO HMT PREMIUM TRACTOR OIL

DESCRIPTION

Servo HMT Premium Tractor Oil is a premium quality, genuine engine oil for HMT Tractors. The oil is designed for the most severe performance requirements of modern, highly rated turbo charged diesel engines. It assures against protection outstanding high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.

PERFORMANCE BENEFITS

- # Reduced engine scuffing & bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear & deposits
- # Suitable for mixed fleet operation.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.
- # Catalytic Converter compatible.

CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	14.0 - 15.0
Viscosity Index, Min.	135
TBN, mg KOH/g	9.5 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051 E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

Servo HMT Premium Tractor Oil is recommended for engines of HMT Tractors.

PERFORMANCE STANDARDS

- API CF4 / SG
- MB 228.1

*

APPLICATION

* ED-L-5 of IS : 13656 - 2002

MANUFACTURERS APPROVAL

Approved as Genuine Oil for HMT Tractors

