SERVO ® PRODUCT DATA SHEET KINETIC ULTRA 2T OIL



GRADES AVAILABLE - KINETIC ULTRA 2T OIL

DESCRIPTION

Kinetic Ultra 2T Oil is low smoke semisynthetic two stroke engine oil developed to meet the critical requirements of high performance two stroke engines manufactured by M/s. Kinetic Motors Ltd and Kinetic Engineering Ltd. It is blended from selected base stocks and additives to minimise spark plug fouling and preignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It contains a diluent for easy mixing with gasoline.

PERFORMANCE BENEFITS

- Low exhaust smoke
- Maintains engine cleanliness
- Minimises spark plug fouling
- Reduces port deposits and ring sticking
- Prevents seizure and scuffing
- Is easily pumpable by oil injection system

APPLICATION

Kinetic Ultra 2T Oil is recommended for lubrication of Kinetic Pride, DX, ZX, Safari and Luna Mopeds. The recommended dosage of Kinetic Ultra 2T Oil is 20 ml of oil per litre of petrol.

PERFORMANCE STANDARDS

Meets

❖ JASO FC specifications.

MANUFACTURERS APPROVAL

M/s. Kinetic Motors Ltd., and Kinetic Engineering Ltd. have approved Kinetic Ultra 2T Oil for their two stroke scooters and mopeds respectively.

CHARACTERISTICS

	Kinetic Ultra 2T Oil
Kinematic Viscosity @ 40°C, cSt	48-70
Flash Point (COC), °C, Min	70
Sulphated Ash, % Wt., Max	0.25

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.