Product Data Sheet

Servo Greenmile 5W-30

Premium Engine Oil for New Generation Petrol Cars/SUVs



Description

Servo Greenmile 5W-30 is Eco-friendly premium engine oil for new generation petrol cars and SUVs. The additive chemistry and dosage are carefully optimized for improved wear protection and piston cleanliness. This delicately balanced composition provides and exceeds tough industry performance standards thus ensuring reliability, emission control, fuel economy and endurance.

Performance, Features and Benefits

- Exhibits very high oxidation stability & improved high temperature deposit protection for pistons
- Excellent sludge control & wear protection
- Enhanced emission control system compatibility & seal compatibility
- Extended drain intervals up to 15,000 kms
- Compatible with Ethanol blended fuels
- Facilitates reduction of Carbon dioxide by 10% in ecosystem leading to reduction in carbon footprints

Application

Servo Greenmile 5W-30 is recommended as a generic Passenger Car Motor Oil for new generation petrol cars and SUVs. The oil is BS-VI compliant and therefore, can be used in all BS VI petrol vehicles requiring API SN performance level oils as well as BS IV & older passenger vehicles.

Approvals / Performance Standards / Recommendations

Servo Greenmile 5W-30 meets the performance requirement of API SN

Typical Physical Characteristics

Servo Greenmile	Method	5W-30
Appearance	Visual	Clear & Bright
Colour	ASTM D-1500	3.0
Flash point COC , °C	ASTM D-92	215
Pour point, °C	ASTM D-97	(-) 39
Kinematic viscosity at 100°C, cST	ASTM D-445	11.02
Viscosity Index	ASTM D-2270	164
HTHS @ 150 °C , cP	ASTM D-5481	3.4
CCS @ -30°C	ASTM D-5293	6005
Total base number , mg KOH/g	ASTM D-2896	10.2
Foam test; Tend/Stab, ml		
Seq. I	ASTM D-892	10/0
Seq. II	ACTIVID 002	20/0
Seq. III		10/0
Sulfated ash , % wt	ASTM D-874	1.05

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at https://cx.indianoil.in/. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

11 AUG 2021

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:
Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051
E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | https://cx.indianoil.in/