

# Product Data Sheet



## SERVO HYPERSPORT F5

Fully Synthetic Premium Four-Stroke Motorcycle Engine Oil

### Description

Servo Hypersport F5 is a premium 4T Motorcycle Oil formulated with high performance fully synthetic base oils and synergistic additive systems for outstanding detergency & dispersancy required for new generation four stroke engines, anti-wear performance for gears and suitable friction performance for clutches to meet latest international standards of motorcycle oils. This delicately balanced formulation exceeds tough industry performance standards thus ensuring reliability, emission control, fuel economy and endurance. Servo Hypersport F5 is designed to provide new experience with enhanced power and acceleration and smooth gear shifting, making it a true biker oil.

### Performance, Features and Benefits

- Enhanced Power and Acceleration for extreme operating conditions
- Durable clutch friction for smooth shifting
- Future ready, meeting API highest standard API SP performance capability
- Enhanced catalyst protection
- Fortified with superior anti-wear additives for enhanced engine & gear durability
- Extended oil drain intervals

### Application

Servo Hypersport F5 is recommended for use in all type of motorcycles including that meeting latest regulations as well as mid-to-high displacement bikes.

### Approvals / Performance Standards / Recommendations

Servo Hypersport F5 in SAE 10W-50 viscometrics meets the engine performance requirements of API SP and friction performance of JASO MA2 (T903:2016).

### Typical Physical Characteristics

Parameters	Method	Value
Appearance	Visual	Clear & Bright
Flash point COC, °C	ASTM D92	250
Pour Point, °C	ASTM D97	-51
Kinematic viscosity at 100°C, cSt	ASTM D445	17.78
Colour	ASTM D1500	2.5
Viscosity Index	ASTM D2270	158
CCS @ -25°C, mPa.s	ASTM D5293	6564
HTHS @ 150°C, mPa.s	ASTM D5481	4.8
Total base number, mg KOH/g	ASTM D2896	6.8
Foam test; Tend/Stab, ml		10/0
Seq. I	ASTM D892	20/0
Seq. II		10/0
Seq. III		
Sulfated ash, % wt	ASTM D874	0.80

### Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

31 MAY 2023

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,

Indian Oil Corporation Ltd.,

G-9, Ali Yavar Jung Marg, Bandra (E),

Mumbai - 400051

E-Mail: [servotechserv@indianoil.in](mailto:servotechserv@indianoil.in) or

[servots@indianoil.in](mailto:servots@indianoil.in) | <https://cx.indianoil.in/>