SERVO ® PRODUCT DATA SHEET SERVO 4T ZOOM



GRADES AVAILABLE - SERVO 4T ZOOM

DESCRIPTION

Servo 4T Zoom is high performance engine oil for 4 stroke 2/3 wheelers. This oil is a high viscosity index, 4 stroke engine oil.

APPLICATION

Servo 4T Zoom is recommended for new generation 4 stroke motorcycles, scooters and auto rickshaws.

PERFORMANCE BENEFITS

- Maximum power output.
- Superior performance in terms of oxidation stability.
- Excellent wear protection at high temperatures and severe operating conditions.
- Outstanding overall engine cleanliness.
- Finhanced engine & gear life.
- Higher fuel efficiency.
- Potential oil drain period of more than 5000 Kms.

PERFORMANCE STANDARDS

JASO T 903 : API SJ / JASO MA 2

CHARACTERISTICS

SAE GRADE	20W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.5
Viscosity Index, Min.	110
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 21
TBN, mg KOH/gm	5.5 – 7.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.