



SERVO 4T

GRADES AVAILABLE - SERVO 4T

<p>DESCRIPTION</p> <p>Servo 4T is high performance engine oil for 4 stroke 2/3 wheelers. This oil is blended from high viscosity index base stocks and contains additives to meet the stated performance standards.</p>	<p>APPLICATION</p> <p>Servo 4T is recommended for new generation 4 stroke motorcycles, scooters and auto rickshaws.</p>
<p>PERFORMANCE BENEFITS</p> <ul style="list-style-type: none"> ☞ Maximum power output. ☞ Superior performance in terms of oxidation stability. ☞ Excellent wear protection at high temperatures and severe operating conditions. ☞ Outstanding overall engine cleanliness. ☞ Enhanced engine life. ☞ Higher fuel efficiency. ☞ Potential oil drain period of 5000 Kms. 	<p>PERFORMANCE STANDARDS</p> <ul style="list-style-type: none"> ○ JASO T903 : API SG / JASO MA 2 <p>MANUFACTURERS APPROVAL</p> <ul style="list-style-type: none"> ☆ M/s Bajaj Auto Ltd. ☆ M/s TVS Motor Co. Ltd. ☆ M/s LML Limited.

CHARACTERISTICS

SAE GRADE	20W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.5
Viscosity Index, Min.	110
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 21
TBN, mg KOH/gm	9.5 – 11.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

