



GRADES AVAILABLE – SERVO HMT TRACTOR OIL 20W-40

DESCRIPTION

Servo HMT Tractor Oil is Multigrade Universal Tractor Oil specifically formulated to meet all the lubrication requirements of tractors. It has a high detergency level and excellent oxidation stability combined with good antiwear and antiweld properties.

APPLICATION

Servo HMT Tractor Oil is recommended a Genuine oil for HMT Tractors for the engine, combined transmission, gear box lubrication and hydraulic system of HMT tractors.

PERFORMANCE BENEFITS

- Excellent all weather performance.
- Prevents wrong use and mixing up of different oils in applications.
- Reduces the inventory of different grades.
- Extends oil and equipment life.

PERFORMANCE STANDARDS

- API CD for engine oil and API GL 4 for gear oil
- US Military MIL-L-45199B for engine oil and MIL-L-2105 for gear oil
- @ E-DL2 of IS:13656-2002
- Caterpillar series 3

MANUFACTURERS APPROVAL

Approved as Genuine oil for HMT Tractors.

CHARACTERISTICS

SAE GRADE	20W-40		
Kin. Viscosity @ 100°C, cSt	14.5 – 16.3		
Viscosity Index, Min	110		
Flash Point, COC, °C, Min	200		
TBN mg KOH/gm	9.5 – 11.5		

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR: