



SERVO PRIDE GEO ALT 20W-50

GRADES AVAILABLE - SERVO PRIDE GEO ALT 20W-50

<p>DESCRIPTION</p> <p>Servo Pride GEO ALT 20W-50 is a high performance low ash gas engine oils, formulated from high quality mineral oil and select additive system to provide excellent thermal stability and resistance to oxidation and nitration.</p>	<p>APPLICATION</p> <p>Servo Pride ALT GEO 20W-50I is recommended for Ashok Leyland commercial vehicles operating CNG.</p>
<p>PERFORMANCE BENEFITS</p> <ul style="list-style-type: none"> ➤ Excellent resistance to oxidation and nitration. ➤ Excellent resistance to corrosion. ➤ Extra protection for valve guide seats against wear. 	<p>PERFORMANCE STANDARDS</p> <p>Servo Pride GEO ALT 20W-50 meets the following specifications.</p> <ul style="list-style-type: none"> ✎ CES 20074 of Cummins USA <p>MANUFACTURERS APPROVAL</p> <ul style="list-style-type: none"> • Ashok Leyland Ltd, Chennai- Oil change every 10,000 Kms.

CHARACTERISTICS

SAE GRADE	20W-50
Kinematic Viscosity cSt @ 100°C	17.5 – 19.5
Viscosity Index, Min.	120
Flash point (COC), °C Min.	200
Pour Point, °C Max.	(-) 21
TBN mg KOH/gm	5-6

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai-400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

